

2026 RK CHAIN APPLICATIONS

CHAIN	NATURAL	GOLD	COLOR	BLACK SCALE	SEAL TYPE	STREET	Dual & Adventure	Enduro & XC / Rally	SX / MX	ROAD RACE	ATV	TENSILE (lbs)	MAX HORSEPOWER	WEAR LIFE‡	WEIGHT* (lbs)	MAX CHAIN WIDTH ** (mm)
ROAD RACE SPECIFIC																
415HRU	-	✓	-	-	U					250		4,800	60 HP	700	1.52	15.4
520XRU	-	✓	-	-	UW					1000		9,000	265 HP	3100	3.44	18.8
DRAG RACE SPECIFIC																
530DR	✓	-	-	-	-					DRAG		10,400	250 HP	100	4.96	24.7
530PRODR	✓	-	-	-	-					DRAG		11,880	350 HP	440	5.12	26.6
STRONGEST ON THE STREET																
520ZXW	-	✓	✓	✓	XW	1200	1200					9,450	200 HP	3800	3.92	20.9
525ZXW	-	✓	✓	✓	XW	1300	1300					10,430	220 HP	4100	4.56	23.5
530ZXW	-	✓	✓	✓	XW	1400	1400					11,200	220 HP	4200	4.89	25.5
LIGHT WEIGHT HIGH PERFORMANCE																
520XRE	✓	✓	-	-	XW	800	800	750			750	8,200	130 HP	3500	3.44	21.7
525XRE	✓	✓	-	-	XW	1000	1000					9,400	200 HP	3900	3.97	22.5
530XRE	✓	✓	-	-	XW	1400	1100					9,900	205 HP	4050	4.65	24.5
ULTRA-THIN-SEALED FOR Mini-Bike																
420MRU	-	-	-	✓	U	150						4,540	35 HP	2400	1.74	17.1
ULTRA-THIN-SEALED FOR VINTAGE BIKE *Up to 750cc, For 2 Cylinder bike up to 1,000 cc																
530UWR	-	-	✓	-	UW	750						9,260	150 HP	3100	4.10	22.7
OFF ROAD / ATV RACE SPECIFIC																
520EXW	✓	✓	-	-	XW		750	750			750	7,700	70 HP	3300	3.70	22.0
OFF ROAD / ENDURO RACE SPECIFIC																
NEW! NEW! 420MXU2	-	✓	-	-	U		150	150	150			4,540	35 HP	2400	1.74	17.1
428MXU	-	✓	-	-	U		150	150	150			6,070	35 HP	2400	2.21	20.2
520MXU	-	✓	-	-	UW		500	500	500			8,000	70 HP	3200	3.04	19.2
PRO MX / SX RACE SPECIFIC - MXZ4/5 Series comes with Hard chrome Coating pin with Extended wear life																
420MXZ4	-	✓	-	-	-		150		150			4,980	40 HP	450	1.73	17.2
428MXZ4	-	✓	-	-	-		150		150			6,400	40 HP	450	2.21	20.2
520MXZ5	-	✓	-	-	-		500		500			8,500	70 HP	450	3.06	19.3
WEEKEND WARRIOR MX / SX																
420MXZ	✓	✓	-	-	-		150		150			4,980	30 HP	200	1.73	17.2
428MXZ1	✓	✓	-	-	-		150		150			6,070	30 HP	200	2.21	20.2
ECONOMICAL SEALED																
520SO	✓	✓	-	-	O	400	400				400	6,900	60 HP	2400	3.39	21.7
MAX SERIES - Maximum performance, Maximum Value																
520MAXO	✓	✓	-	-	O	800	650				650	8,500	130 HP	2400	3.51	21.4
525MAXO	✓	✓	-	-	O	900	750					9,300	150 HP	2400	4.38	23.9
530MAXO	✓	✓	-	-	O	1000	750					9,700	150 HP	2400	4.77	25.7
520MAXX	✓	✓	✓		RX	1000	750				750	9,000	120 HP	3600	4.02	22.0
525MAXX	✓	✓	✓		RX	1100	900					9,300	175 HP	3700	4.38	23.9
530MAXX	✓	✓	✓		RX	1100	900					9,700	180 HP	3700	4.77	25.7
520MAXZ	✓	✓	✓		RX	1200	1200					9,400	200 HP	3600	4.18	21.3
525MAXZ	✓	✓	✓		RX	1300	1300					10,420	220 HP	4000	4.68	23.5
530MAXZ	✓	✓	✓		RX	1400	1400					11,200	220 HP	4000	4.99	25.5
HEAVY DUTY																
M415H	✓	-	-	-	-	125	80					4,100	20 HP	200	1.59	14.6
M420H	✓	-	-	-	-	125	90					4,100	15 HP	200	1.79	16.9
M428H	✓	-	-	-	-	200	125					5,400	15 HP	200	2.22	20.3
M520H	✓	-	-	-	-	400	250					7,700	30 HP	200	3.51	19.7
M525H	✓	-	-	-	-	500						7,700	40 HP	200	3.73	21.3
M530H	✓	-	-	-	-	500						7,700	40 HP	200	4.17	22.9
530KS	✓	-	-	-	-	400						7,100	60 HP	200	3.75	21.9
STANDARD																
M420	✓	-	-	-	-	125	90					4,000	10 HP	100	1.65	16.2
M428	✓	-	-	-	-	150	125					4,500	12 HP	100	1.85	18.9
M520	✓	-	-	-	-	250	250					6,800	20 HP	100	3.28	18.5
M525	✓	-	-	-	-	400						6,800	30 HP	100	3.51	19.9
M530	✓	-	-	-	-	400						6,800	30 HP	100	3.73	21.7

RK recommends using a chain model with the maximum amount of displacement and horsepower ratings based on motorcycle's original equipped chain size.

‡ = WEAR LIFE figure is a comparison between RK Chain models. Baseline is RK's non-sealed standard chains at 100.

* Wear life should not be used to compare other brand of chains

* = LBS/100 Links

**= Need a wider amount of space than the maximum chain width in order to install the chain.